

It's SIMPLE



go & click

This simple operation oven is a very convenient device for the users that do not require complex programming features. Easy operation is based on a simple controller that features temperature adjustment option with set 0-72 hours or continuous operation.

click & go



1. set temp.
2. set time
3. start work

Technical data:

Parameter	Model	SLN 53 SIMPLE	SLW 53 SIMPLE	SLN 115 SIMPLE	SLW 115 SIMPLE
air convection		natural	forced	natural	forced
chamber capacity ¹	[l]	56	56	112	112
	[cu ft]	2	2	3,9	3,9
door type		solid			
temperature range	[°C]	5° above ambient temperature...+250°			
	[°F]	9° above ambient temperature...+482°			
controller		microprocessor with external display			
interior		stainless steel according to DIN 1.4016			
housing		powder coated sheet			
overall dims* [mm]	width	595	595	655	655
	height	700	700	845	845
	depth	600	600	700	700
internal dims [mm]	width	395	395	460	460
	height	395	395	540	540
	depth	360	360	450	450
max shelf workload [kg]		10	10	10	10
max unit workload [kg]		40	40	60	60
nominal power [W]		1600	1600	2400	2400
weight [kg]		50	50	65	65
temperature resolution [°C]		every 0,1			
temperature variation ² [°C]	at 70°C	±1,9	±0,8	±1,0	±0,6
	at 150°C	±3,2	±2,2	±2,9	±2,3
	at 250°C	±7,1	±4,2	±7,2	±4,5
temperature fluctuation ³ [°C]	at 70°C	±0,5	±0,2	±0,6	±0,2
	at 150°C	±0,9	±0,3	±1,2	±0,3
	at 250°C	±1,7	±0,4	±1,3	±0,4
over temperature protection		class 1.0 according to DIN 12880			
voltage 50 /60 Hz [V]		115/230			
shelves fitted / max ⁴		2/5	2/5	2/7	2/7
warranty		24 months			
manufacturer		POL-EKO-APARATURA			

* - dims of power cable (50 mm) not included

1 - working capacity of chamber can be smaller

2 - spatial measurement

3 - measured in centre of the chamber

4 - "fitted" - number of shelves fitted, included in price, "max" - number of shelves which can be fitted

MANUFACTURER:

POL-EKO-APARATURA sp.j.
ul. Kokoszycka 172C
44 - 300 Wodzisław Śląski
POLAND

Tel: +48 32 453 91 70

Fax: +48 32 453 91 85

e-mail: export@pol-eko.com.pl

www.polekolab.com

